



32 x 8
D3.1

TC4400

Ultra-Broadband Cable Modem
for above Gigabit speeds

CABLE

DATA

The TC4400 is the first DOCSIS® 3.1 cable modem introduced by Technicolor offering data services beyond Gigabit speeds.

■ Highest Performance with DOCSIS 3.1

The TC4400 matches perfectly with the requirements of cable operators willing to propose ultimate Broadband access to their customers.

The TC4400 cable modem is fully compliant with the latest DOCSIS 3.1 specification as published by CableLabs® and is capable of delivering downstream cable speeds of up to 4 Gbps by using 2 Orthogonal Frequency-Division Multiplexing (OFDM) downstream channels and up to 1 Gbps upstream by using 2 Orthogonal Frequency-Division Multiple Access (OFDMA) upstream channels.

This enhanced and superior performance allows Cable Operators to propose multi-Gigabit data services to their customers through various applications, from IP connectivity to ultra-high speed internet access and gaming.

■ Future Proof High-Bandwidth Technology

The TC4400 can be deployed by cable operators on their current network, seamlessly integrating as a DOCSIS 3.0 cable modem offering 32 bonded downstream and 8 bonded upstream channels.

Once cable operators upgrade their network to the new DOCSIS 3.1 standard, the TC4400 supports this migration without any need of intervention at the customer premises due to some of its unique features such as:

- DOCSIS/EuroDOCSIS 3.0 backwards compatibility
- a fully integrated 1.2 GHz full band capture Wideband tuner
- a switchable diplexer that allows to support existing band split as well as future DOCSIS 3.1 band split on the same hardware.

■ Advanced Security

To secure data exchange between the cable modem and the cable operators' servers, BPI+ communications privacy is used.

■ Easy to Use

Like all Technicolor modems and gateways, the TC4400 is an easy to use, easy to install device.

For convenience of the end user, the easy-to-access LEDs provide a clear indication of start-up sequence, operational status, and connectivity status.

Multiple integrated web pages also allow direct access to the status and settings, including privacy and security information.

■ ECO

Technicolor is committed to offer its customers sustainable products and implements a set of ECO features to reach the best possible environmental performance. In addition to carefully selected plastics and packaging to minimize the ecological footprint, the TC4400 benefits from a unique combination of hardware and software features that reduce power consumption substantially.

Features at a Glance

- DOCSIS® 3.1 compliant
- Backward compatible with (Euro)DOCSIS® 3.0
- 2 x 2 OFDM(A) bonded channels in DOCSIS 3.1 mode
- 32 x 8 bonded channels in DOCSIS 3.0 mode
- Switchable diplexer for upstream and downstream frequency up to 204 MHz split
- 1.2 GHz full band capture tuner
- Built in RF spectrum analyzer
- 2 GE LAN ports
- IPv4, IPv6 DS-Lite
- Designed to meet the latest ECO standards

TC4400

Ultra-Broadband Cable Modem
for above Gigabit speeds

Technical Specifications

Hardware

■ Interfaces WAN	1 RF connector F-Type
■ Interfaces LAN	2 10/100/1000 Base-T Ethernet ports
■ Buttons	Reset button
■ Power input	DC jack
■ Power supply	12 VDC external PSU
■ AC Voltage	120 - 240 VAC, 50 - 60 Hz (switched mode PSU)
■ Dimensions	163 x 53 x 145 mm (8.42 x 2.09 x 5.71 in.)
■ Operating temperature	0° - 40° C (32° - 104° F)
■ Storage temperature	-20° - 70° C (-4° - 158° F)
■ Operating humidity	5 - 95 % non-condensing

Cable certifications

■ Data	DOCSIS® 3.1 compliant
■ CMTS interoperability	Any qualified DOCSIS 3.1 CMTS Any qualified (Euro)DOCSIS® 3.0 CMTS

Cable receiver

■ Downstream modulation	64, 256, 1024, 4096 QAM
■ Downstream frequency range, software selectable	DOCSIS 3.0 54 - 1002 MHz 108 - 1002 MHz EuroDOCSIS 3.0 108 - 1218 MHz 258 - 1218 MHz
■ Number of downstream channels	DOCSIS 3.1 2 OFDM (Euro)DOCSIS 3.0 Up to 32 bonded
■ Maximum downstream data range	DOCSIS 3.1 Up to 4 Gbps DOCSIS 3.0 1372 Mbps (theoretical 42.88 Mbps x 32) EuroDOCSIS 3.0 1780 Mbps (theoretical 55.62 Mbps x 32)
■ Capture windows	1.2 GHz full band capture
■ Channel bandwidth	DOCSIS 3.1 max. 192 MHz bands DOCSIS 3.0 6 MHz EuroDOCSIS 8 MHz
■ Input signal level range	-15 dBmV / + 15 dBmV
■ Input impedance	75 Ohm

Cable transmitter

■ Upstream modulation	QPSK 8, 16, 32, 64 and 128 QAM
■ Upstream frequency range, software selectable	DOCSIS 3.0 5 - 42 MHz 5 - 85 MHz EuroDOCSIS 3.0 5 - 85 MHz 5 - 204 MHz
■ Number of upstream channels	DOCSIS 3.1 2 OFDMA (Euro)DOCSIS 3.0 Up to 8 bonded
■ Maximum upstream data range	262 Mbps (theoretical 32.78 Mbps x 8)
■ Channel bandwidth	200, 400 and 800 kHz, 1.6, 3.2 and 6.4 MHz
■ Output impedance	75 Ohm
■ Upstream spectral analyzer	

TC4400

Ultra-Broadband Cable Modem
for above Gigabit speeds

Technical Specifications

Management

- User-friendly GUI via HTTP
- Command Line Interface (CLI)
 - Telnet
 - SSH v2
- SNMP
 - SNMP v1, SNMP v2, SNMP v3
- Operation, Administration & Maintenance (OAM)
 - ITU-T Y.1731
- Software upgrade
 - via WAN RF connection only
- Logging and alert

Networking

- Routing modes
 - Transparent bridging
- Multiple client support
 - 32
- Class of services
 - 16 downstream IDs
 - 16 upstream service flows
- Network protocol
 - IP (IPv4, IPv6 DS-Lite)
 - TCP, UDP, ARP
 - ICMP, DHCP
 - TFTP, SNMP, HTTP, Telnet
- Protocol filtering
 - Ethernet and IP

Quality of Service

- Traffic type prioritization
 - DOCSIS 1.0, 1.1 compliant
- IEEE 802.1Q classification
- Queuing, policing, shaping

Security

- Baseline Privacy Interface Plus (BPI+)

ECO design

- Power control features
 - Power reduction schemes built-in

Package contents

- TC4400
- Ethernet cable (RJ-45)
- Power supply unit
- Quick Setup leaflet(s) (optional)
- Safety Instructions & Regulatory Information booklet



Professional Services

To reinforce our extensive portfolio of digital home solutions, Technicolor has a dedicated Professional Services team to make sure that every deployment is a success, from initial provisioning and integration to operations, upgrades, ongoing support and beyond. Our wide array of services spans the entire customer project lifecycle, encompassing:

- Expert consulting
- Software customizations and customer change orders
- Qualified technical support and maintenance
- Seamless system integration
- Efficient repair, refurbishment and recycling
- Warranty extensions on all our products

TECHNICOLOR WORLDWIDE HEADQUARTERS

1-5, rue Jeanne d'Arc - 92130 Issy-les-Moulineaux, France
Tel: +33 (0)1 41 86 50 00 - Fax: +33 (0)1 41 86 58 59

www.technicolor.com

SALES CONTACT

For more information please get in touch with your usual sales representative or use the following email:

contactsales@technicolor.com



FEEL THE WONDER